

251

WARNING AND LOCATION TAPES

PRODUCT DESCRIPTION

Backing:

- LDPE.

Colour:

- red, blue, yellow, orange.

Thickness:

- 0.08 mm red, blue, yellow, orange,
- 0.20 mm red, blue,
- 0.30 mm red, blue,
- 0.40 mm red, blue,
- 0.50 mm red, blue.
-

Width:

- 200 mm,
- other dimensions upon request.

Length:

- 100 m.

Product meets the applicable restrictions of RoHS Directive and REACH regulations.



ANTICOR Sp. z o.o. holds ISO 9001:2015 certificate.

251

Marking tape.

APPLICATION

- In the gas industry for marking the course of gas pipeline routes, available in **yellow**.
- In the power industry for marking cable routes, available in **blue** (up to 1 kV) and **red** (above 1 kV). The colours and thickness of the tapes used to mark power networks are consistent with the standards depending on the rated voltage of the network.
- In water supply systems for marking the course of water supply network routes, available in **blue**.
- In telecommunications for marking and locating telecommunications cables, available in **orange**.

FEATURES AND ADVANTAGES

- Yellow colored tapes are produced in accordance with the **ZN-G-3002:2001** standard, update **ST-IGG-1002:2011**.
- Orange tapes have the opinion of the **ZDBŁ in Warsaw**.
- Tapes with a thickness of ≥ 0.3 mm have an approval for compliance with the **SEP-E-04** standard.

USAGE

- Marking tape should be placed at least 30 cm over electric cable or pipeline in the ground.

STORAGE

- Store the product in dry area in original packaging.
- Protect the cartons against mechanical damage.
- The recommended storage temperature: up to 25°C.