


Aluminio 360-17

ALUMINIUM TAPES

TAPE STRUCTURE



PRODUCT DESCRIPTION

Backing:

- Soft aluminium foil.

Adhesive:

- Butyl rubber.

Liner:

- PE-foil.

Colour:

- Printed silver.

Aluminio 360-17

Heavy duty foil-butyl aluminum tape.

APPLICATION

- Indoor or outdoor sealing of low, medium and high-pressure HVAC duct systems (includes metal duct, fiberglass duct and flexible duct systems).
- Sealing cracks & seams in gutters, roof valleys, eaves, ridges, around chimneys & vent stacks, leaks in vans, cars & trucks.
- Repair gouges, rips, tears in metal panels of trailers, shipping containers & metal buildings, mobile home repair.
- Repair in aluminium siding, sheet metal, gutters, storage buildings, flashing, containers, greenhouses, and more.

TECHNICAL DATA		
Physical Properties	Unit	Value
Total thickness	mm	0.432
Backing thickness	mm	0.051
Temperature range	°C	-28 ÷ 93
Tensile strength	N/cm	min. 35.03
Adhesion to steel	N/cm	min. 21.88
Elongation	%	-

Product meets the applicable restrictions of RoHS Directive and Reach regulations.



ANTICOR Sp. z o.o. holds ISO 9001:2015 certificate.

FEATURES AND ADVANTAGES

- Weather and UV resistant.
- Provides instant water and air-tight seal.
- Resistant to moisture and solvents.
- Permanent repairs.
- Remains in place in low temperature as long as necessary.
- Conforms easily to round, square, or odd-shapes objects.
- Easy to use in tight spaces.
- Ability to cover by paint.
- Sgressive adhesive is made of butyl rubber, contains no bitumen.
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®.
- Low VOC content (Volatile Organic Compound).

USAGE

- Apply to the dry, clean, and degreased surface, free from other contaminants.
- Optimal application temperature: +10 ÷ 40°C.
- During application use tension and pressure to smooth the tape by hand.

STORAGE

- Store the product in dry area in original packaging.
- Protect the cartons against mechanical damage.
- The recommended storage temperature: up to 25°C.