


# 621

## INDUSTRIAL TAPES

### TAPE STRUCTURE



### PRODUCT DESCRIPTION

#### Backing:

- Embossed PVC.

#### Adhesive:

- Rubber.

#### Colour:

- Yellow.

### 621

PVC masking tape – embossed.

### APPLICATION

- Protection with plastering, carpentry during joinery and painting.
- Effective protection during painting and making colour patterns of external walls.
- Masking and joining elements outside or inside buildings, suitable especially for masking during plastering.

### FEATURES AND ADVANTAGES

- UV resistant.
- Resistant to chemicals, moisture and aging.
- Waterproof.
- Easy to apply.
- Easy to tear during application without cutting tools (no cutting tools necessary).
- High tensile strength.
- During outside application doesn't leave adhesive stains until 21 days (in "full sun exposition").

Product meets the applicable restrictions of RoHS Directive and Reach regulations.



ANTICOR Sp. z o.o. holds ISO 9001.

### USAGE

- Apply to the dry, clean and degreased surface, free from other contaminants.
- Optimal application temperature: 10 ÷ 40°C.
- During application use tension and pressure to smooth the tape by hand.

### STORAGE

- To ensure the maximum product performance, store products in a dry, ventilated area in original packaging away from direct sunlight.
- Protect the products in original packaging against mechanical damage.
- The recommended storage temperature: -5 ÷ 40°C.