

252

WARNING AND LOCATION TAPES

PRODUCT DESCRIPTION

Banking:

- LDPE.

Colour:

- red, blue, yellow, brown, orange.

Thickness:

- 0.08 mm (red, blue, brown, orange)
- 0.30 mm (yellow)

Width:

- 200 mm,
- other dimensions upon request.

Length:

- 100 m

Product meets the applicable restrictions of RoHS Directive and REACH regulations.



ANTICOR Sp. z o.o. holds the ISO 9001:2015 certificate.

252

Marking tape with the inscription.

APPLICATION

- In the gas industry for marking the course of gas pipeline routes, available in **yellow**.
- In the power industry for marking cable routes, available in **blue** (up to 1 kV) and **red** (above 1 kV). The colours and thickness of the tapes used to mark power networks are consistent with the standards depending on the rated voltage of the network.
- In water supply and sewage systems for marking the water supply or sewage network for early warning of the existence of the above-mentioned network, available in **blue** and **brown**.
- In telecommunications for marking and locating telecommunications cables, available in orange and with an imprint:
 - ATTENTION TELECOMMUNICATION CABLE,
 - ATTENTION FIBER OPTIC CABLE,
 - ATTENTION OPTOTELECOMMUNICATION CABLE.
- For district heating, for marking the district heating network, available in **yellow** and **purple**.

FEATURES AND ADVANTAGES

- Yellow coloured tapes are produced in accordance with the **ZN-G-3002:2001** standard, update **ST-IGG-1002:2011**.
- Orange tapes have the opinion of the **ZDBL** in Warsaw.
- Tapes with a thickness of ≥ 0.3 mm have an approval for compliance with the **SEP-E-04** standard.
- Cable tape available up to a thickness of 0.5 mm.
- Tapes available with an imprint, eg
 - CAUTION CABLE, CAUTION CABLE 110 kV,
 - CAUTION CABLE at a depth of 0.5 ÷ 1.0 m
 - POWER CABLE.

USAGE

- Marking tape should be placed at least 30 cm over electric cable or pipeline in the ground.

STORAGE

- Store the product in dry area in original packaging.
- Protect the cartons against mechanical damage.
- The recommended storage temperature: up to 25°C.

Copyrights ANTICOR Sp. z o.o. All rights reserved.

REV3-082021