

# ANTICOR Plast 745

## CORROSION PROTECTION

### PRODUCT DESCRIPTION

ANTICOR Plast 745 mass is manufactured basing on deeply refined mineral oil, hydrocarbons thickener with corrosion inhibitors and adhesion-improving components.

Colour: Sahara.

### TECHNICAL DATA

Parameters	Unit	Value
Density at 20°C	kg/dm <sup>3</sup>	~1.4
Flash-point	°C	200
Operating temperature	°C	up to 30

Product holds the certificate of the DVGW Institute, the attestation of the National Institute of Hygiene and building mark „B”.

Product is the element of corrosion protection system in A30 class EN 12068. ANTICOR Plast system contains the following components:

- ANTICOR Plast 745 mastic
- ANTICOR Plast 701-40 tape, 2x50% overlap
- ANTICOR Plast 732-08 protection tape, 1x50% overlap



ANTICOR Sp. z o.o. holds the ISO 9001 certificate

### ANTICOR Plast 745

Corrosion protection mass for A30 class according to EN 12068.

### APPLICATION

- For surface irregularity filling.
- For irregular profile and dimension levelling and smoothing as a corrosion protection of T-joints, flanges and muff joints, pipe fittings and joints.

### FEATURES & ADVANTAGES

- Easy to apply.
- It contains corrosion inhibitors and adhesion improving components.
- Resistant to moisture, it does not dissolve in water.
- Does not contain ingredients harmful to health and the environment (Certified by the National Institute of Hygiene).

### USAGE

- Plasticize the mass by kneading in your hands.
- Apply with trowel on surface cleaned from contaminants, dust, rust and moisture.

### STORAGE

- Store the product in dry area in original packaging.
- Protect the cartons against mechanical damage.
- The recommended storage temperature: up to 25°C.

### PRODUCT FORM & SIZE AVAILABLE

PE bag: 2 kg.