


# Instal Band 490-30

## CORROSION PROTECTION

### TAPE STRUCTURE



### PRODUCT DESCRIPTION

**Backing:**

- Reinforced cloth.

**Adhesive:**

- Petroleum plastic mass with corrosion inhibitors.

**Colour:**

- Olive.

TECHNICAL DATA		
Parameters	Unit	Value
Total thickness	mm	≥0.8
Operating temperature	°C	up to 30
Adhesion to steel	-	cohesive



ANTICOR Sp. z o.o. holds the ISO 9001 certificate.

### Instal Band 490-30

Corrosion protection plastic tape.

### APPLICATION

- For sealing joints of sewer pipes.
- For corrosion protection of underground steel pipeline components: pipes, fittings, valves and flanges and welded.
- To secure underground terminals installation of lightning protection and grounding before electrochemical corrosion.

### FEATURES & ADVANTAGES

- The unique anticorrosion mass containing corrosion inhibitors based on mineral oil.
- The base oil with corrosion inhibitors constantly affects protected surface penetrating its structure.
- Do not change its properties throughout the period of use (does not harden).
- Compatible with bituminous and PE insulations.
- Easy and fast to apply.
- Moisture resistant.
- High electric strength.
- Does not contain ingredients harmful to health and the environment.

### USAGE

- Apply to the dry, clean and degreased surface.
- Wrap the tape around the surface spirally stretching a bit, with 50% overlap, this process repeat twice. If combining with the existing insulation it is necessary to make 10 cm overlap of the existing coating.
- During application smooth the tape surface by hand.
- Optimal application temperature: 10 ÷ 30°C.

### STORAGE

- Store the product in dry area in original packaging.
- Protect the cartons against mechanical damage.
- The recommended storage temperature: up to 25°C.

### PRODUCT FORM & SIZE AVAILABLE

Cut rolls: 30, 50, 100 mm x 10 m, other sizes available on individual request.