

ANTICOR Seal 511

SEALING MATERIALS

PRODUCT DESCRIPTION

ANTICOR Seal 511 - is a synthetic viscoelastic material with sealing properties. It has high adhesion to concrete, ceramic, metal surfaces and plastics. ANTICOR Seal does not change its properties over a period of use (does not harden).

It doesn't contain hazardous substances to the health and the environment.

TECHNICAL DATA

Physical Properties	Unit	Value
Operating temperature	°C	-15 ÷ 50
Density	kg/dm ³	1.46
Water absorption	% _{mas}	< 0.035
Tensile strength	kV	7.2
Volume resistivity	Ωm	1.4*10 ¹²
Flash point	°C	>238
Adhesion to concrete and plastics	Cohesive fracture (tearing in the layer)	

Product meets the applicable restrictions of RoHS Directive and Reach regulations.

Packaging: Tube 310 ml



ANTICOR Sp. z o.o. holds the ISO 9001 certificate.

ANTICOR Seal 511

Used for:

- Sealing and filling external and underground electrical cable boxes and cables in protection pipes, etc.
- Sealing and filling around cable conduits and pipe passes through walls.
- Sealing and corrosion protection.

FEATURES AND ADVENTAGES

- Synthetic product of exceptional sealing properties.
- Viscoelastic, does not harden, **always plastic**.
- Corrosion protection properties.
- Dielectric properties.
- High adhesion to concrete, ceramic, metal surfaces and plastics.
- Requires minimal surface preparation.
- Easy and fast application.
- Tightly fills the whole space, prevents and blocks the access of water and moisture from inside the building.
- Free of components hazardous to human health and natural environment.
- Use in low voltage up to 1000 V.

APPLICATION

!!! Product should be preheated to a temperature of 30 ÷ 40°C before application.

Application by a caulking gun for tubes (310 ml).