


# Polytex 119

## INDUSTRIAL TAPES

### TAPE STRUCTURE



### PRODUCT DESCRIPTION

#### Backing:

- Foil PE laminated cotton cloth.

#### Adhesive:

- Synthetic rubber.

#### Colour:

- White, black, blue, green, red, yellow.

### Polytex 119

Professional duct tape for different applications.

### APPLICATION

- Holding, securing, seaming, repairing, bundling, splicing, packaging, masking and as moisture barrier.
- Marking on the floor in industrial hall communication lines, safety zone etc.
- Joining and tightening thermal insulation.
- Tightening air-conditioning and ventilating ducts.

### FEATURES AND ADVENTAGES

- High tensile strength.
- Very good adhesion.
- Aggressive tack.
- Waterproof backing.
- Good handling characteristics.
- Resists twisting or curling.
- Well fits into irregular profiles and surfaces.
- No cutting tools necessary.
- Non-staining

Product meets the applicable restrictions of RoHS Directive and Reach regulations.



ANTICOR Sp. z o.o. holds the ISO 9001:2015 certificate.

### USAGE

- Apply to the dry, clean and degreased surface, free from other contaminants.
- Optimal application temperature: 10÷40°C.
- During application use tension and pressure to smooth the tape by hand.

### STORAGE

- Store the product in dry area in original packaging.
- Protect the cartons against mechanical damage.
- The recommended storage temperature: up to 25°C.

### PRODUCT FORM & SIZE AVAILABLE

48 mm x 50 m, other sizes available on individual request.