


# ELECTRIX 211

## ELECTROTECHNICAL TAPES

### TAPE STRUCTURE



### PRODUCT DESCRIPTION

**Backing:**

Plasticized PVC.

**Adhesive:**

- Synthetic rubber.

**Colour:**

- Black, red, blue, brown, violet, white, green, yellow, gray, yellow-green.

### TECHNICAL DATA

Physical Properties	Unit	Value
Total thickness	mm	0.13
Voltage value	V	up to 600
Dielectric strength	kV/mm	min. 40
Temperature range	°C	to 80
Tensile strength	N/cm	min. 15
Adhesion to steel	N/cm	min. 1.0
Elongation	%	min. 150

Product meets the applicable restrictions of RoHS Directive and Reach regulations, is VDE certified.



ANTICOR Sp. z o.o. holds the ISO 9001:2015 certificate.

### ELECTRIX 211

PVC Electrical Tape.

### APPLICATION

- Wrapping and waterproofing wire harnesses.
- Repairing damaged isolations.
- Isolation and bundling of wires.
- Marking wires by colors.

### FEATURES AND ADVANTAGES

- Weather resistance.
- Waterproof.
- Self-extinguishing.
- High adhesion.
- Very flexible, convenient to use.
- Excellent electrical insulation.

### USAGE

- Apply to the dry, clean, and degreased surface, free from other contaminants.
- Optimal application temperature:  $10 \div 40^{\circ}\text{C}$ .
- Wrap the tape with min. 50% overlap.
- During application use tension and pressure to smooth the tape by hand.

### STORAGE

- Store the product in dry area in original packaging.
- Protect the cartons against mechanical damage.
- The recommended storage temperature: up to  $25^{\circ}\text{C}$ .

### PRODUCT FORM & SIZE AVAILABLE

15 mm x 10 m, 19 mm x 20 m, other sizes available on individual request.