


# ANTICOR Plast 732-08

## CORROSION PROTECTION

### TAPE STRUCTURE



### PRODUCT DESCRIPTION

**Backing:**

- PVC film.

**Adhesive:**

- Rubber based adhesive.

**Colour:**

- Yellow, blue, black.

### ANTICOR Plast 732-08

Mechanical protection tape for A30 class according to EN 12068.

### APPLICATION

- As a mechanical corrosion protection applied on the basic corrosion protection layer of ANTICOR Plast 701-40 tape.

### FEATURES & ADVANTAGES

- Highly flexible and elastic, perfectly adapts to the surface of irregular shapes and surfaces.
- Fast and easy application.
- Frost resistant.
- Weather resistance, including UV.
- Resistant to attrition, moisture, and ageing.
- Provides a minimum vapor permeability.

### USAGE

- Condition the tape before application at 10÷25 °C.
- Apply on the basic corrosion protection layer of ANTICOR Plast 701-40 plastic tape.
- Optimal application temperature: 10÷30°C.
- Wrap the tape with min. 50% overlap.
- During application use tension and pressure to smooth the tape by hand.

### STORAGE

- Store the product in dry area in original packaging.
- Protect the cartons against mechanical damage.
- The recommended storage temperature: up to 25°C.

### PRODUCT FORM & SIZE AVAILABLE

50 mm x 20 m, other sizes available on individual request.

### TECHNICAL DATA

Parameters	Unit	Value
Total thickness	mm	0.19
Dielectric strength	kV/mm	min. 40
Temperature range	°C	to 80
Tensile strength	N/cm	min. 25
Adhesion to steel	N/cm	min. 1.75
Elongation	%	min. 180

Product holds the certificate of the DVGW Institute, the attestation of the National Institute of Hygiene and building mark „B”.

Product is the element of corrosion protection system in A30 class (according to EN 12068). ANTICOR Plast system contains the following components:

- ANTICOR Plast 745 mastic
- ANTICOR Plast 701-40 tape, 2x50% overlap
- ANTICOR Plast 732-08 protection tape, 1x50% overlap



ANTICOR Sp. z o.o. holds the ISO 9001:2015 certificate.