

**SAFETY DATA SHEET**  
In accordance with Regulation (EU) 2020/878  
**POLYKEN 1027 Primer**

Compilation date: 07.09.2010

Revision: 19.03.2025

Version: 6.1 ENG

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1. Product identifier**

Trade name: **POLYKEN 1027 Primer**  
Contains: Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  
UFI: EC00-Y0HA-500P-F4HP

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Identified uses: POLYKEN adhesive coating.

Uses advised against: not specified.

**1.3. Details of the supplier of the safety data sheet**

Supplier: ANTICOR Sp. z o.o.  
Address: Wygoda 28, 32-020 Wieliczka, Poland  
Telephone No/Fax No: +48 12 288 33 33 / +48 12 278 53 26  
E-Mail: anticor@anticor.pl

**1.4. Emergency telephone number**

+48 12 288 33 33 (available from Monday till Friday during office hours: 8 am – 4 pm)  
112 (24h)

**SECTION 2: HAZARDS IDENTIFICATION**

**2.1. Classification of the substance or mixture**

Hazard	Classification	According to Regulation (EC) no. 1272/2008
for physical-chemical properties:		Flam. Liq. 2, H225 Highly flammable liquid and vapour.
for health hazards:		Skin Irrit. 2, H315 Causes skin irritation. Eye Irrit. 2, H319 Causes serious eye irritation. STOT SE 3, H336 May cause drowsiness or dizziness.
for environmental hazards:		Aquatic Chronic 2, H411 Toxic to aquatic life with long lasting effects.

**2.2. Label elements**

Hazard pictogram(s): GHS02  GHS07  GHS09 

Signal word(s): Danger

Hazard statement(s):

H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statement(s):

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.



**SAFETY DATA SHEET**  
In accordance with Regulation (EU) 2020/878  
**POLYKEN 1027 Primer**

Compilation date: 07.09.2010

Revision: 19.03.2025

Version: 6.1 ENG

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container to a licensed waste collector in accordance with local/regional/national/international regulation.

### 2.3. Other hazards

The product does not contain components that are classified as PBT/vPvB.

The product does not contain components that are included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 % by weight.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

Substance name	% mass	Product identifier	Regulation (EC) No 1272/2008 (CLP)	
			Hazard class	H-phrases
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	50 - 75	CAS nr: none EC nr: 920-750-0 Index nr: Not applicable Registration nr: 01-2119473851-33-xxxx	Flam. Liq. 2 Asp. Tox. 1 Skin Irrit. 2 Eue Irrit. 2 STOT SE 3 Aquatic Chronic 2	H225 H304 H315 H319 H336 H411
Xylene, mixture of isomers	10 - 19	CAS nr: 1330-20-7 EC nr: 215-535-7 Index nr: 601-022-00-9 Registration nr: Not available	Flam. Liq. 3 Acute Tox. 4 Acute Tox. 4 Skin Irrit. 2 Eye Irrit. 2 Aquatic Chronic 2	H226 H312 H332 H315 H319 H411
n-hexane	>0 - <3	CAS nr: 110-54-3 EC nr: 203-777-6 Index nr: 601-037-00-0 Registration nr: Not available	Flam. Liq. 2 Repr. 2 Asp. Tox. 1 STOT RE 2 Skin Irrit. 2 Eye Irrit. 2 STOT SE 3 Aquatic Chronic 2	H225 H361f H304 H373 H315 H319 H336 H411 STOT RE 2; H373: C $\geq$ 5%
Methanol	>0 - <3	CAS nr: 67-56-1 EC nr: 200-659-6 Index nr: 603-001-00-X Registration nr: Not available	Flam. Liq. 2 Acute Tox. 3 Acute Tox. 3 Acute Tox. 3 STOT SE 1 Skin Irrit. 2 Eye Irrit. 2	H225 H331 H311 H301 H370 H315 H319 STOT SE 1; H370: C $\geq$ 10% STOT SE 2; H371: 3% $\leq$ C < 10%
Cyclohexane	>0 - 3	CAS nr: 110-82-7 EC nr: 203-806-2 Index nr: 601-017-00-1 Registration nr: Not available	Flam. Liq. 2 Asp. Tox. 1 Skin Irrit. 2 STOT SE 3 Aquatic Acute 1 Aquatic Chronic 1	H225 H304 H315 H336 H400 (M=1) H410 (M=1)
Zinc oxide	>0 - <0,3	CAS nr: 1314-13-2 EC nr: 215-222-5 Index nr: 030-013-00-7 Registration nr: Not available	Eye Irrit. 2 Aquatic Acute 1 Aquatic Chronic 1	H319 H400 (M=10) H410 (M=10)
3-iodo-2-propynyl butylcarbamate	>0 - <0,1	CAS nr: 55406-53-6 EC nr: 259-627-5 Index nr: 616-212-00-7 Registration nr: Not available	Acute Tox. 4 Acute Tox. 3 Eye Dam. 1 Skin Sens. 1 STOT RE 1 Aquatic Acute 1 Aquatic Chronic 1	H302 H331 H318 H317 H372 (larynx) H400 (M=10) H410 (M=1)

Page 2 of 9



**SAFETY DATA SHEET**  
In accordance with Regulation (EU) 2020/878  
**POLYKEN 1027 Primer**

Compilation date: 07.09.2010

Revision: 19.03.2025

Version: 6.1 ENG

Ethylbenzene	>0 - <0,1	CAS nr: 100-41-4 EC nr: 202-849-4 Index nr: 601-023-00-4 Registration nr: Not available	Flam. Liq. 2 Acute Tox. 4 Asp. Tox. 1 STOT RE 2 Eye Irrit. 2 Aquatic Chronic 2	H225 H332 H304 H373 (hearing organs) H319 H411
4-(1,1,3,3-tetramethylbutyl)phenol	>0 - <0,1	CAS nr: 140-66-9 EC nr: 205-426-2 Index nr: 604-075-00-6 Registration nr: Not available	Acute Tox. 4 Skin Irrit. 2 Eye Dam. 1 Aquatic Acute 1 Aquatic Chronic 1	H312 H315 H318 H400 (M=10) H410 (M=10)
Formaldehyde	>0 - <0,01	CAS nr: 50-00-0 EC nr: 200-001-8 Index nr: 605-001-00-5 Registration nr: Not available	Acute Tox. 3 Acute Tox. 3 Acute Tox. 2 Skin Corr. 1B Eye Dam. 1 Skin Sens. 1 Muta. 2 Carc. 1B STOT SE 3 Aquatic Acute 1 Aquatic Chronic 1	H301 H311 H330 H314 H318 H317 H341 H350 H335 H400 (M=1) H410 (M=1) Eye Irrit. 2; H319: 5 % ≤ C < 25 % STOT SE 3; H335: C ≥ 5 % Skin Corr. 1B; H314: C ≥ 25 % Skin Irrit. 2; H315: 5 % ≤ C < 25 % Skin Sens. 1; H317: C ≥ 0,2 %

The text of the H-phrases is shown in section 16 of the safety data sheet.

#### SECTION 4: FIRST AID MEASURES

##### 4.1. Description of first aid measures

###### Inhalation:

Remove victim to fresh air. When any symptoms persists get medical attention.

###### Contact with skin:

Wash skin thoroughly with soap and water, then flush with a plenty of water. Do not use neutralizing agents. When an irritation persists get medical attention.

###### Contact with eyes:

Flush eyes with plenty of water for at least 15 minutes holding the eyelids open, remove contact lenses if present. Do not use neutralizing agents. When an irritation persists, consult an ophthalmologist.

###### Ingestion:

Do NOT induce vomiting. Rinse mouth with water. Get medical attention.

##### 4.2. Most important symptoms and effects, both acute and delayed

Inhalation: headache, nausea, dizziness, disturbance in consciousness.

Contact with skin: irritation, redness.

Contact with eyes: irritation, redness, tearing.

Ingestion: gastrointestinal disorders.

##### 4.3. Indication of any immediate medical attention and special treatment needed

As a general rule, in case of doubt or if symptoms persist, always call a doctor. Do not give anything to eat or drink to an unconscious person. Do not induce vomiting. Show the safety data sheet or label/ packaging to a person providing first aid. Treat symptomatically.

#### SECTION 5: FIREFIGHTING MEASURES

##### 5.1. Extinguishing media

**Suitable Extinguishing Media:** water spray, foam, powder, carbon dioxide.



**SAFETY DATA SHEET**  
In accordance with Regulation (EU) 2020/878  
**POLYKEN 1027 Primer**

Compilation date: 07.09.2010

Revision: 19.03.2025

Version: 6.1 ENG

**Unsuitable Extinguishing Media:** water jets.

**5.2. Special hazards arising from the substance or mixture**

Gas/vapour spreads at floor level: ignition hazard. May build up electrostatic charges: risk of ignition. Upon combustion CO and CO<sub>2</sub> are formed.

**5.3. Advice for firefighters**

Cool tanks/drums with water spray/remove them into safety. Do not move the load if exposed to heat. Prevent from entering contaminated water into sewers, rivers or other bodies of water. Dispose of waste water in compliance with current legislation. People should be properly trained and equipped with proper clothing and safety equipment. Use fire resistant protective clothing, breathing apparatus and eye protection.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Use adequate personal protective equipment as required in Section 8 of the safety data sheet. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Remove sources of ignition. Avoid breathing vapour or mist. Provide adequate ventilation.

**6.2. Environmental precautions**

Prevent soil and water pollution. Prevent spreading in sewers. Contain released product, pump over in suitable containers. Plug the leak, cut off the supply. Dam up the liquid spill. Try to reduce evaporation. Inform the relevant authorities if the product has caused environmental pollution.

**6.3. Methods and material for containment and cleaning up**

Stop leaks from the container. Spillage cover with an inert material eg. earth, sand, vermiculite, diatomite and then collect to a labelled container. Do not use compressed air for pumping over spills. Dispose of waste in compliance with current legislation. Wash the contaminated area in plenty of water.

**6.4. Reference to other sections**

Refer to Sections 8 and 13 of the safety data sheet.

**SECTION 7: HANDLING AND STORAGE**

**7.1. Precautions for safe handling**

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Handle uncleaned empty containers as full ones. Never eat, drink or smoke during use. Always wash hands with soap and water before and after work. Use adequate personal protective equipment as required in Section 8 of the safety data sheet. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Provide adequate ventilation.

**7.2. Conditions for safe storage, including any incompatibilities**

Store in cool area, in tightly closed, properly labelled original containers. Ventilation at floor level. Keep away from heat sources, ignition sources, oxidizing agents.

**7.3. Specific end use(s)**

Not known.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control parameters**

Poland:

Xylene, mixture of isomers: NDS: 100 mg/m<sup>3</sup>, NDSCh: 200 mg/m<sup>3</sup>, NDSP: - (dermal)

Ethylbenzene: NDS: 200 mg/m<sup>3</sup>, NDSCh: 400 mg/m<sup>3</sup>, NDSP: - (dermal)

Methanol: NDS: 100 mg/m<sup>3</sup>, NDSCh: 300 mg/m<sup>3</sup>, NDSP: - (dermal)

Cyclohexane: NDS: 300 mg/m<sup>3</sup>, NDSCh: 1000 mg/m<sup>3</sup>, NDSP: - (dermal)

n-hexane: NDS: 72 mg/m<sup>3</sup>, NDSCh: -, NDSP: - (dermal)



**SAFETY DATA SHEET**  
In accordance with Regulation (EU) 2020/878  
**POLYKEN 1027 Primer**

**Compilation date: 07.09.2010**

**Revision: 19.03.2025**

**Version: 6.1 ENG**

Formaldehyde: NDS: 0,37 mg/m<sup>3</sup>, NDSch: 0,74 mg/m<sup>3</sup>, NDSP: - (dermal)  
Zinc oxide – calculated as Zn – inhalable fraction: NDS: 5 mg/m<sup>3</sup>, NDSch: 10 mg/m<sup>3</sup>, NDSP: -

EU OELs:

Xylene, mixture of isomers: TWA 8h: 221 mg/m<sup>3</sup>, 50 ppm; STEL 15 min.: 442 mg/m<sup>3</sup>, 100 ppm (dermal)

Ethylbenzene: TWA 8h: 442 mg/m<sup>3</sup>, 100 ppm; STEL 15 min.: 884 mg/m<sup>3</sup>, 200 ppm (dermal)

Methanol: TWA 8h: 260 mg/m<sup>3</sup>, 200 ppm; STEL 15 min.: - (dermal)

Cyclohexane: TWA 8h: 700 mg/m<sup>3</sup>, 200 ppm; STEL 15 min.: -

n-hexane: TWA 8h: 72 mg/m<sup>3</sup>, 20 ppm; STEL 15 min.: -

Formaldehyde: TWA 8h: 0,5 mg/m<sup>3</sup>, 0,62 ppm; STEL 15 min.: 0,74 mg/m<sup>3</sup>, 0,6 ppm

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

DNEL workers, long term exposure, systemic, dermal: 773 mg/kg bw/day

DNEL workers, long term exposure, systemic, inhalation: 2035 mg/m<sup>3</sup>

DNEL consumer, long term exposure, systemic, dermal: 699 mg/kg bw/day

DNEL consumer, long term exposure, systemic, inhalation: 608 mg/m<sup>3</sup>

DNEL consumer, long term exposure, systemic, oral: 699 mg/kg bw/day

## 8.2. Exposure controls

### Appropriate engineering controls:

Measure the concentration of OELs in the air regularly. Work under local exhaust/ventilation

### Eye/face protection:

Protective goggles or face shield (EN166).

### Skin protection:

Protective gloves made of nitrile rubber or PVA (EN374). Wear suitable protective clothing, head/neck protection.

### Respiratory protection:

Gas mask with filter type A or ABEK (EN143) when exposure limits are exceeded or lack of appropriate ventilation.

### Thermal hazards:

Not known.

### Environmental exposure controls:

Precautions should be made against environmental contamination.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

a) Physical state	: Liquid
b) Colour	: Black
c) Odour	: Characteristic, petroleum-like
d) Melting point/freezing point	: Not available
e) Boiling point or initial boiling point and boiling range	: ≥100°C
f) Flammability	: Highly flammable liquid and vapour
g) Lower and upper explosion limit	: 0,6% / 7,1%
h) Flash point	: 6°C (closed cup, DIN 53213)
i) Auto-ignition temperature	: Not applicable
j) Decomposition temperature	: Not available
k) pH	: Not available
l) Kinematic viscosity	: Not available
m) Solubility	: Insoluble in water
n) Partition coefficient n-octanol/water (log value)	: Not available
o) Vapour pressure	: Not available
p) Density and/or relative density	: 0,85 g/cm <sup>3</sup>
q) Relative vapour density	: Not available
r) Particle characteristics	: Not applicable



**SAFETY DATA SHEET**  
In accordance with Regulation (EU) 2020/878  
**POLYKEN 1027 Primer**

Compilation date: 07.09.2010

Revision: 19.03.2025

Version: 6.1 ENG

**9.2. Other information**

Not available.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1. Reactivity**

The mixture is not reactive.

**10.2. Chemical stability**

The mixture is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

**10.3. Possibility of hazardous reactions**

Not known.

**10.4. Conditions to avoid**

Sources of ignition. Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

**10.5. Incompatible materials**

Oxidizing agents.

**10.6. Hazardous decomposition products**

Not known. Hazardous combustion products are listed in Section 5 of the safety data sheet.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity:**

Based on available data, the classification criteria are not met.

ATE mix oral: >2000 mg/kg

ATE mix dermal: >2000 mg/kg

ATE mix inhalation: >20 mg/l

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

LD50: 5840 mg/kg (oral, rat)

LD50: 2920 mg/kg (dermal, rat)

LC50: 23,3 mg/l (4h, inhalation, rat)

**Skin corrosion/irritation:**

Causes skin irritation.

**Serious eye damage/irritation:**

Causes serious eye irritation.

**Respiratory or skin sensitisation:**

Based on available data, the classification criteria are not met.

**Germ cell mutagenicity:**

Based on available data, the classification criteria are not met.

**Carcinogenicity:**

Based on available data, the classification criteria are not met.

**Reproductive toxicity:**

Based on available data, the classification criteria are not met.

**STOT-single exposure:**

May cause drowsiness or dizziness.

**STOT-repeated exposure:**

Based on available data, the classification criteria are not met.

**Aspiration hazard:**

Based on available data, the classification criteria are not met.



**SAFETY DATA SHEET**  
In accordance with Regulation (EU) 2020/878  
**POLYKEN 1027 Primer**

Compilation date: 07.09.2010

Revision: 19.03.2025

Version: 6.1 ENG

**11.2. Information on other hazards**

Endocrine disrupting properties: not applicable.  
Other hazards: not known.

**SECTION 12: ECOLOGICAL INFORMATION**

**12.1. Toxicity**

Toxic to aquatic life with long lasting effects.  
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:  
NOEL: 6,3 mg/l (72h, algae)  
NOEL: 3 mg/l (96h, fish)

**12.2. Persistence and degradability**

Data not available

**12.3. Bioaccumulative potential**

Mixture: BCF: not available.

**12.4. Mobility in soil**

Data not available

**12.5. Results of PBT and vPvB assessment**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6. Endocrine disrupting properties**

None.

**12.7. Other adverse effects**

WGK : 2 (Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 4))

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1. Waste treatment methods**

Waste code: 08 01 11\* - waste paint and varnish containing organic solvents or other dangerous substances  
15 01 10\* - packaging containing residues of or contaminated by dangerous substances

Recycle or dispose of waste in compliance with current legislation. Remove to an authorized plant for the destruction, neutralization and elimination of hazardous waste. Do not discharge into surface water or drains.

Packaging: Recycle or dispose of waste in compliance with current legislation.

Directive 2008/98/EC of the European Parliament and of the Council of the Member State.

**SECTION 14: TRANSPORT INFORMATION**

**14.1. UN number or ID number**

UN 1133

**14.2. UN proper shipping name**

ADHESIVES containing flammable liquid

**14.3. Transport hazard class(es)**

3

**14.4. Packing group**

II

**14.5. Environmental hazards**

Yes. Marine pollutant

**14.6. Special precautions for user**

Limited quantities: 5L

**14.7. Maritime transport in bulk according to IMO instruments**

Not applicable

**SECTION 15: REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing





**SAFETY DATA SHEET**  
In accordance with Regulation (EU) 2020/878  
**POLYKEN 1027 Primer**

**Compilation date: 07.09.2010**

**Revision: 19.03.2025**

**Version: 6.1 ENG**

Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

Candidate List - SVHC: not applicable

Annex XIV REACH (authorization)

Annex XVII REACH (restrictions): 3, 40.

## **15.2. Chemical safety assessment**

Chemical safety assessment has not been carried out for the mixture by a supplier - it is not required.

## **SECTION 16: OTHER INFORMATION**

### **Classification method:**

Flam. Lig. 2, H225- based on flash point

Skin Irrit. 2, H315 – calculation method.

Eye Irrit. 2, H319 – calculation method.

STOT SE 3, H336 – calculation method.

Aquatic Chronic 2, H411 – calculation method.

### **Changes made in the safety data sheet during revision:**

Section: 3, 8.1, 16.

### **Legend to abbreviations and acronyms used in the safety data sheet:**

NDS Occupational Exposure Limit (Poland)

NDSch Short-term Occupational Exposure Limit (Poland)

NDSP Threshold limit value – ceiling (Poland)

OELs Occupational Exposure Limits

vPvB Very persistent and very bioaccumulative (substance)

PBT Persistent, bioaccumulative and toxic (substance)

PNEC Predicted No Effect Concentration

DNEL Derived No Effect Levels

BCF Bioconcentration factor

LD50 Dose of a tested substance causing 50% lethality during a specified time interval

LC50 Lethal Concentration 50%, concentration required to kill half the members of a tested population after a specified test duration

EC50 Concentration of a substance in an environmental medium expected to produce a certain effect in 50% of test organisms in a given population under a defined set of conditions

NOEL No observed effect level

### **Literature references and sources for data:**

Regulations/legislations mentioned in sections 2 – 15 of safety data sheet. Information supplied by the manufacturer (sds v.8.04).

### **List of relevant hazard statements and/or precautionary statements, which are not written out in full under Sections 2 to 15:**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.





**SAFETY DATA SHEET**  
In accordance with Regulation (EU) 2020/878  
**POLYKEN 1027 Primer**

Compilation date: 07.09.2010

Revision: 19.03.2025

Version: 6.1 ENG

H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H361f	Suspected of damaging fertility.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Advice on any training appropriate for workers to ensure protection of human health and the environment:**

Workers that use the product should be trained and informed about personal protection, accident procedure, etc.

**Exposure scenarios:** data is included in sections of the SDS.

*Information in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. Information provided herein serves only as guidelines for safe work, use, processing, storage, and waste management. It cannot be considered as a warranty or quality certificate. This information applies only to specific material designated and may not be suitable for such material used in combination with any other materials or in any other manner not described in this document.*

Prepared by **Mia-Che** [www.mia-che.pl](http://www.mia-che.pl) for ANTICOR Sp. z o.o.

