


Rubber Foam Tape 600

INDUSTRIAL TAPES

TAPE STRUCTURE



PRODUCT DESCRIPTION

Backing:

- Synthetic rubber foam reinforced with PET mesh.

Adhesive:

- Acrylic.

Liner:

- Silicone paper, brown.

Colours:

- Black.

TECHNICAL DATA

Parameters	Unit	Value	Test method
Total thickness	mm	3,08	PSTC-133/ASTM D 3652
Backing thickness	mm	3	PSTC-133/ASTM D 3652
Density	kg/cm ³	min. 67	GB/T611-2021
Adhesion to steel	Rozierwanie nośnika		PSTC-101/ASTM D 3330
Initial adhesion test	cm	2,5	PSTC-6/ASTM D 3121
Reaction to fire		B-s1, d0	EN 13501-1:2019
Risk of corrosion		neutral ph	EN 13468
Temperature range	°C	-30 ÷ 60	-

Product meets EN 14304:2009+A1:2013 standard.



ANTICOR Sp. z o.o. holds the ISO 9001:2015 certificate.

PET Scrim Reinforced Rubber Foam Tape type 600

Single-sided adhesive PREMIUM synthetic rubber foam reinforced with polyester mesh.

APPLICATION

- Fixing and sealing duct and pipe connections with foam in HVAC systems.
- Thermal insulation of building equipment and industrial installations.
- Acoustic insulation of pipes and ducts, preventing the transmission of vibrations, dampening noise and vibrations.
- Waterproofing, protection against moisture and corrosion.

FEATURES AND ADVANTAGES

- Single-sided adhesive, flexible.
- Excellent adhesion.
- Frost-resistant - coated with low-temperature acrylic adhesive.
- Resistant to weathering (including UV), moisture, and aging.
- Resistant to water vapor diffusion.
- Resistant to stretching.
- PET mesh reinforcement increases mechanical strength, bond durability, and dimensional stability.
- Easy application.

USAGE

- Apply to a dry, clean, degreased surface, free of other contaminants. To achieve excellent adhesion, the tape should not be applied under excessive pressure; apply appropriate pressure with your hand or a squeegee.
- Optimal application temperature: 10 ÷ 40°C.
- Shelf life: 12 months.

STORAGE

- Store the product in dry area in original packaging.
- Protect the cartons against mechanical damage.
- Humidity: 50% relative humidity.
- The recommended storage temperature: up to 21°C.

PRODUCT FORM & SIZE AVAILABLE

- 3 mm x 50 mm x 15 m
- 3 mm x 100 mm x 15 m